

Bearing Designation	Dimensions(mm/in)										Ball Diameter	Load Rating	Weight
轴承型号	尺寸(mm/英寸)										钢球直径	载荷(KN)	重量
	d+0.03 -0.01	B	C1	d2	d3 UNF-2B	h1	L3	(L4)	d4	sw			≈ kg
CF3	4.826	7.92	5.94	15.88	10-32	26.97	11.11	34.91	10.31	7.92	13	7.6	0.182
CF3	0.19	0.312	0.234	0.625	10-32	1.062	0.437	1.375	0.406	0.312	13	7.6	0.182
CF4	6.35	9.53	6.35	19.05	4/28	33.32	14.28	42.85	11.89	9.52	18	9.9	0.226
CF4	0.25	0.375	0.25	0.75	4/28	1.312	0.562	1.687	0.468	0.375	18	9.9	0.226
CF5	7.938	11.1	7.92	22.23	5/16	34.92	15.88	46.03	12.7	11.1	14	12.7	0.362
CF5	0.3125	0.437	0.312	0.875	5/16	1.375	0.625	1.812	0.5	0.437	14	12.7	0.362
CF6	9.525	12.7	9.11	25.4	8/24	41.28	19.05	53.98	17.45	14.27	14	17	0.059
CF6	0.375	0.5	0.359	1	8/24	1.625	0.75	2.125	0.687	0.562	14	17	0.059
CF7	11.112	14.27	10.31	28.58	7/16	46.02	22.22	60.3	19.05	15.88	13	21	0.081
CF7	0.4375	0.562	0.406	1.125	7/16	1.812	0.875	2.375	0.75	0.625	13	21	0.081
CF8	12.7	15.88	11.5	33.33	2/20	53.98	25.4	70.64	22.22	19.05	12	27.5	0.131
CF8	0.5	0.625	0.453	1.312	2/20	2.125	1	2.781	0.875	0.75	12	27.5	0.131
CF10	15.875	19.05	12.29	38.1	8/18	63.5	31.75	82.55	25.4	22.22	16	29.9	0.195
CF10	0.625	0.75	0.484	1.5	8/18	2.5	1.25	3.25	1	0.875	16	29.9	0.195
CF12	19.05	22.23	15.06	44.45	4/16	73.02	38.1	95.25	28.58	25.4	14	44.2	0.294
CF12	0.75	0.875	0.593	1.75	4/16	2.875	1.5	3.75	1.125	1	14	44.2	0.294
CF16	25.4	34.93	25.4	69.85	4/12	104.78	53.98	139.7	41.28	38.1	14	129.1	0.925
CF16	1	1.375	1	2.75	4/12	4.125	2.125	5.5	1.625	1.5	14	129.1	0.925