

| Designation | d1·d2[mm] |     | d1·d2 standard aperture&corresponding transmission of torque |    |     |       |    |    |    |     |     | Cinch bolt |                |     | Rotational inertia     |
|-------------|-----------|-----|--|----|-----|-------|----|----|----|-----|-----|------------|----------------|-----|------------------------|
| 型号          | d1·d2[mm] |     | d1·d2标准孔径[mm]和相应的可传递的扭矩 [N·m]                                |    |     |       |    |    |    |     |     | 胀紧螺栓       |                |     | 转动惯量                   |
|             | min       | max | D  | dH | L   | L1,L2 | L3 | E  | B  | S   | a   | M          | Locking torque | M1  |                        |
|             | 最小        | 最大  |  |    |     |       |    |    |    |     |     |            | 锁紧扭矩 [N·m]     |     | [kg·m <sup>2</sup> ]   |
| LC-ES-040S  | 10        | 20  | 40   | 18 | 66  | 25    | 18 | 16 | 12 | 2   | 3   | M4         | 3.4            | M4  | 0.44x10 <sup>-4</sup>  |
| LC-ES-055S  | 14        | 28  | 55   | 27 | 78  | 30    | 22 | 18 | 14 | 2   | 3   | M5         | 7              | M5  | 1.91x10 <sup>-4</sup>  |
| LC-ES-065S  | 15        | 38  | 65   | 30 | 90  | 35    | 27 | 20 | 15 | 2.5 | 4   | M5         | 7              | M5  | 4.18x10 <sup>-4</sup>  |
| LC-ES-080S  | 20        | 45  | 80   | 38 | 114 | 45    | 35 | 24 | 18 | 3   | 4   | M6         | 14             | M6  | 12.9x10 <sup>-4</sup>  |
| LC-ES-095S  | 25        | 50  | 95   | 46 | 126 | 50    | 35 | 26 | 20 | 3   | 4   | M8         | 30             | M8  | 31.7x10 <sup>-4</sup>  |
| LC-ES-105S  | 30        | 55  | 105  | 51 | 140 | 56    | 41 | 28 | 21 | 3.5 | 4   | M10        | 68             | M10 | 52.0x10 <sup>-4</sup>  |
| LC-ES-120S  | 35        | 70  | 120  | 60 | 160 | 65    | 45 | 30 | 22 | 4   | 4.5 | M10        | 68             | M10 | 103.0x10 <sup>-4</sup> |
| LC-ES-135S  | 40        | 70  | 135  | 68 | 185 | 75    | 55 | 35 | 26 | 4.5 | 4.5 | M12        | 118            | M12 | 191.0x10 <sup>-4</sup> |
| LC-ES-160S  | 42        | 80  | 160  | 80 | 210 | 85    | 63 | 40 | 30 | 5   | 5   | M12        | 118            | M12 | 369.8x10 <sup>-4</sup> |