

Designation	Rated torque [N·m]	最大容许误差 Margin of error		Moment of inertia	The torque stiffness	The axial spring rigidity	Radial spring rigidity	Weight	A	B	C	D1/2	E(Locking torque)		F	G	H	I	K	
		Eccentricity [mm]	Deflection										E (螺栓锁紧扭矩 N·m)							
型号	额定扭矩 [N·m]	偏心 [mm]	轴向位移 [m·m]	惯性力矩 [10-3N·m/rad]	扭矩刚性 [103N·m/rad]	轴向弹簧刚性 [N/mm]	径向弹簧刚性 [N/mm]	质量 [kg]												
LC-F4-15-47	15	0.15	1	0.1	20	25	475	0.25	47	49	19	10-22	M4	3.3	M4	20	8.5	11	4	
LC-F4-15-54	15	0.2	2	0.12	15	15	137	0.25	54	49	19	10-22	M4	3.3	M4	20	8.5	11	4	
LC-F4-30-68	30	0.2	1	0.22	39	50	900	0.4	68	55	22	12-23	M4	6	M4	27	22	16	5	
LC-F4-30-76	30	0.25	2	0.27	28	30	270	0.4	76	55	22	12-23	M4	6	M4	27	22	16	5	
LC-F4-60-72	60	0.2	1.5	0.58	76	72	1200	0.8	72	66	27	12-29	M5	8	M5	30	18	16	5	
LC-F4-60-82	60	0.25	2	0.61	55	48	420	0.8	82	66	27	12-29	M5	8	M5	30	18	16	5	
LC-F4-80-81	80	0.2	2	0.97	129	48	920	1.2	81	81	32	15-37	M5	10	M5	30	20	16	5	
LC-F4-80-93	80	0.25	3	1.3	85	32	290	1.2	93	81	32	15-37	M5	10	M5	30	20	16	5	